

CNTX-30-T

CONTRAST SENSOR

Increase process throughput with high-speed, accurate and reliable contrast differentiation. The CNTX™ combines a broad-spectrum light source, small spot size and fast response to achieve high-speed contrast differentiation of both neutral and color targets. The CNTX employs our field-proven, patented technology, for effective detection of registration marks, glossy surfaces, cap inserts, date codes and sorting of product by color in many industrial applications. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

The CNTX provides simple, two-button teach with mark and background keys. The flexibility of the CNTX makes it easy to set-up in a wide variety of printing, packaging and converting applications. The CNTX is a perfect fit for many applications that require the ability to differentiate between two conditions that vary in contrast.

The CNTX includes both a discrete PNP/NPN output and an analog output. The discrete output is automatically set for PNP or NPN operation. The analog output signal may be used to access targets based on their reflectance characteristics.

CNTX



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com
www.emxinc.com



Applications

- Sort products by color
- Detect registration marks
- Confirm presence of date codes
- Detection of glossy surfaces
- Detects cap inserts

Design & Features

- 3.0mm spot size
- 25uS response time
- Two-button teach
- Broad spectrum white LED
- Automatic LED intensity adjustment
- PNP/NPN
- Discrete output
- Analog output
- Small size

Ordering Information



CNTX-30-T
Contrast Sensor

Accessories



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F

NOT INTENDED FOR USE IN
PERSONAL SAFETY APPLICATIONS.

Functions

OPERATING MODE
MARK
BACKGROUND
RED LED ON
GREEN LED ON
YELLOW LED ON
RED FLASHING
GREEN FLASHING
YELLOW FLASHING

The CNTX-30-T is in operating mode in detect or undetect state
Sets mark level
Sets background level
Mark detected
Background detected
Mark or background measurement in progress
Background set, measure mark
Mark set, measure background
Insufficient contrast

Specifications

White Light source	Broad spectrum LED, min. 100,000 hours	Indicators	
Sensing distance	28mm	Green LED	Power
Spot size	3.0mm dia.	Red LED	Detect
Depth of field	+/- 3mm	Yellow LED	Program
Response time	25uS	Connector M12	
Switching Frequency	40kHz	Pin 1	Power 10 to 24VDC
LED intensity	3 levels	Pin 2	Analog output 0 to 5V DC
Sensitivity	1X, 10X	Pin 3	Ground
Digital Output	Auto-Detect NPN/PNP	Pin 4	Discrete output PNP/NPN
Security	LOCK/UN-LOCK keypad	Pin 5	Remote LOCK/ UNLOCK input
Background indicator	Green LED		
Detect indicator	Red LED		
Programming indicator	Yellow LED		
Data retention	EEPROM non—volatile memory		
Dimensions	2.0" (51mm) x 2.4" (61mm) x 1.0" (25mm)		
Weight	0.21 lbs. (95g)		
Supply Voltage	10-24 VDC		
Operating Current	60 mA		
Short Circuit Protection	Discrete output		
Overload / Reverse Polarity Protection	Supply voltage		
Operating temperature	-20°C...55°C		
Storage temperature	-20°C...70°C		
Housing	Metal alloy		
Mechanical Protection	IP65 NOT FOR PRESSURE WASH DOWN		

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.