AUTOMATIC DATA CAPTURE

QUICKSCAN™ LITE QW2100



GENERAL PURPOSE CORDED HANDHELD LINEAR IMAGER BAR CODE READER

The QuickScan[™] reader series is Datalogic ADC's value line of general purpose handheld data collection products. The QuickScan[™] Lite QW2100 linear imager is an entry level product created specifically for reading long and truncated bar codes which is common in some areas of the world. It is perfect for use in retail, light manufacturing, document/bill processing and banking/finance environments.

The QW2100 imager is small, lightweight and its ergonomic design is comfortable to use during daily operations. It offers snappy reading performance on most 1D bar codes and features a wide scanning angle with an extended scanning line which is perfect for capturing longer and wider bar codes typically found on utility bills and used by manufacturers of electronic parts. Additionally, the scanning line is thinner and brighter, allowing users to scan at wide angles without having to increase the scanning distance.

The QW2100 imager features Datalogic's exclusively patented 'Green Spot' technology for good-read feedback directly on the code. When the reader is in Stand Mode, the Green Spot remains on to show the operator where to position the code for quick and intuitive reading.

A specially designed stand has been created for the QW2100 imager which is light in weight, collapsible to use as a holder instead of a stand, and also has a 'tiltable head' for various angle settings.

GREEN

The QW2100 imager is available with two interface options: USB or Keyboard Wedge / RS-232 and includes various packaging options so that it can be ordered as a scanner only or as a kit equipped with a scanner, cable and stand to facilitate hands-free reading options. The Datalogic Aladdin™ configuration software provides user-friendly features that simplify the start-up procedure, even for inexperienced users.

Because this imager was created for specific areas of the world, please check with your Datalogic Representative to inquire if the QW2100 imager is available in your area.

FEATURES

- Wide scan angle
- Laser-like thinner and extended scan line
- Datalogic Green Spot for good-read feedback
- Two interface options: USB or Keyboard Wedge / RS-232
- Built with over molded rubber to protect the imager when dropped
- Compact and multi-position stand
- Water and Particulate Sealing Rating: IP42
- Drop Resistance to 1.5 m / 5.0 ft
- Uses the same cables and power supplies as the current QuickScan products
- Bulk packaging available (10 scanners per box)
- USB Certified Kits available





SPECIFICATIONS

QUICKSCAN™ LITE QW2100

DECODING CAPABILITY

1D / LINEAR CODES	Autodiscriminates all standard 1D codes including
	GS1 DataBar™ linear codes
POSTAL CODES	Australian Post; British Post; Canadian Post; China Post;
	Japanese Post; KIX Post; Korea Post; Planet Code; Postnet;
	Royal Mail Code (RM4SCC)
STACKED CODES	EAN/JAN Composites; GS1 DataBar Composites; GS1
	DataBar Expanded Stacked; GS1 DataBar Stacked; GS1
	DataBar Stacked Omnidirectional

5 VDC +/- 0.5 V

100.000 lux

16 kV

IP42

5 - 95%

concrete surface

READING RANGES

TYPICAL DEPTH OF FIELD	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. 5 mils : 2.5 to 15.0 cm / 1.0 to 6.0 in 7.5 mils : 0 to 24.0 cm / 0 to 9.4 in 10 mils: 0 to 35.0 cm / 0 to 13.8 in 13 mils: 0 to 40.0 cm / 0 to 15.7 in 20 mils: 0 to 60.0 cm / 0 to 23.6 in
SAFETY & REGULATORY	
AGENCY APPROVALS	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a list of certifications. Complies to China RoHS; Complies to EU RoHS
UTILITIES	
DATALOGIC ALADDIN™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JAVAPOS	JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at not charge.
WARRANTY	
WARRANTY	3-Year Factory Warranty

INTERFACES

TEMPERATURE

INPUT VOLTAGE

ENVIRONMENTAL

ESD PROTECTION (AIR DISCHARGE)

PARTICULATE AND WATER SEALING

HUMIDITY (NON-CONDENSING)

DROP RESISTANCE

INTERFACES

QW2170-BK: RS-232 / Keyboard Wedge QW2120-BK: USB

Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

Operating (Typical): 340 mA @ 5 VDC Standby/Idle (Typical): 190 mA @ 5 VDC

Withstands repeated drops from 1.5 m / 5.0 ft onto a

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE DIMENSIONS WEIGHT Black 17.0 x 6.5 x 7.0 cm / 6.7 x 2.5 x 2.7 in 119.0 g / 4.2 oz

READING PERFORMANCE

LIGHT SOURCE PRINT CONTRAST RATIO (MINIMUM) READ RATE (MAXIMUM) READING ANGLE READING INDICATORS

RESOLUTION (MAXIMUM) FIELD OF VIEW Red LED 610-650 nm 25% 400 reads/sec. Pitch: +/- 65°; Roll (Tilt): +/- 45°; Skew (Yaw): +/- 70° Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED; Good Transmission 0.102 mm / 4 mils (1D Codes) 56° +/- 2°







© 2011 - 2012 Datalogic ADC, Inc. • All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic ADC, Inc. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. and the Datalogic Automatic Data Capture logo is a trademark of Datalogic S.p.A. • Datalogic ADC, Inc. • Datalogic Automatic Data Capture logo is a trademark of Datalogic S.p.A. • Datalogic ADC, Inc. • International laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic S.p.A. • Datalogic and the Datalogic Automatic Data Capture logo is a trademark of Datalogic S.p.A. • Datalogic Alddin is a trademark of Datalogic ADC Group S.r.I. • QuickScan is a registered trademark of Datalogic ADC, Inc. in many countries, including the U.S. and the E.U. • All other brand and product names are trademarks of their respective owners. • DS-QUICKSCANLITE-QW2100-ENA4 20120105